
NRGC-EIP



NRG controller with EtherNet/IP™ Communication



Main features

- **Communication interface.** The NRG controller bridges the field level devices to the control level to allow exchange of data in real-time with the NRG solid state relays.
- **Reduced maintenance costs and downtime.** Use of real-time data for prevention of machine stoppages during operation.
- **Good quality products and low scrap rates.** Real-time monitoring allows timely decisions for better machine and process management.
- **Reduced efforts in troubleshooting.** A number of faults can be distinguished to facilitate and reduce troubleshooting time.
- **Fast installation and set-up.** Control, monitoring and diagnostics all possible via the communication system.
- **Compact dimensions.** One controller with a product width of 35 mm can handle up to 32 switched poles of the RG..CM..N solid state relays.

Description

The **NRGC-EIP** is the NRG controller in the NRG BUS chain.

The **NRGC-EIP** interfaces directly with the main controller of the system through EtherNet/IP communication. Each **NRGC-EIP** is identified by a unique MAC address which is printed on the façade of the product.

The **NRGC-EIP** is mainly a facilitator of the communication between the main controller and each individual RG..N solid state relay in the system. The **NRGC-EIP** also performs internal operations to setup and maintain the internal bus.

The **NRGC-EIP** needs to be supplied with 24 VDC. LEDs on the front facade give a visual indication of the status of the **NRGC-EIP**, of any ongoing communication with the main controller and the RG..Ns on the BUS chain and of any alarm condition related specifically to the **NRGC-EIP**.

Specifications are noted at 25°C unless otherwise specified.


Applications

Any heating application where reliable and precise maintenance of temperatures is crucial to the quality of the end product. Typical applications include plastic machinery such as injection machines, extrusion machines and PET blow moulding machines, packaging machinery, sterilisation machinery, drying tunnels and semiconductor manufacturing equipment.

Main function

- Communication interface: EtherNet/IP
- Connects up to 32 switched poles of the **RG..CM..N** solid state relays
- Supply voltage 24 VDC +/-20%

The NRG system



System Overview

The NRG is a system consisting of one or more BUS chains that enable communication between the field devices (such as the solid state relays) and the control devices (such as the machine controller or PLC).

Each NRG BUS chain consists of the following 3 components:

1. the NRG controller (NRGC..)
2. the NRG solid state relay(s) (RG..N)
3. the NRG internal BUS cables (RCRGN-XXX-2)

The NRG controller is the interface to the machine controller and determines the communication protocol used. It is not possible to operate the NRG system without the NRG controller.

The NRG controllers available are:

- **NRGC** - NRG controller with a Modbus RTU interface over RS485.
- **NRGC-PN** - NRG controller with a PROFINET communication interface. The NRGC-PN is identified by a unique MAC address which is printed on the facade of the product. The GSD file can be downloaded from www.gavazziautomation.com
- **NRGC-EIP** - NRG controller with an EtherNet/IP communication interface. The IP address is provided automatically via a BOOTP server. The EDS file can be downloaded from www.gavazziautomation.com
- **NRGC-ECAT** - NRG controller with an EtherCAT communication interface. The ESI file can be downloaded from www.gavazziautomation.com
- **NRGC-MBTCP** - NRG controller with a Modbus TCP communication interface.

The NRG solid state relay is the switching and monitoring component in the NRG system. Each RG..N integrates a communication interface to exchange data with the machine controller (or PLC). The available RG..Ns that can be used in an NRG system are:

- **RG..D..N**

  The RG..D..N are solid state relays for use in an NRG system having the communication interface only for real time monitoring. Control of the RG..N is done via a DC control voltage. It is possible to have max. 48 x RG..D..Ns in one NRG BUS chain.

System Overview (continued)

- **RG..CM..N**

  The RG..CM..N are solid state relays for use in an NRG system having a communication interface for control of the RG..N through the BUS and for real-time monitoring. Different variants of the RG..CM..N can be mixed on the buschain with a maximum limit of 32 switched poles. The variants of the RG..CM..N are:

  - RGx1A..CM..N – 1-pole solid state relay with zero cross switching.
  - RGx1P..CM..N – 1-pole solid state relay with proportional switching.
  - RGC2P..CM..N – 2-pole solid state contactors with proportional switching.
  - RGC3P..CM..N – 3-pole solid state contactor with proportional switching.

For a review of the features and compatibilities across all variants refer to the table below:

Feature		RGx1A..D..N	RGx1A..CM..N	RGx1P..CM..N	RGC2P..N	RGC3P..N
COMMUNICATION PROTOCOLS	Modbus RTU	●	●	●	●	●
	Modbus TCP	-	●	●	●	●
	PROFINET	-	●	●	●	●
	EtherNet/IP	-	●	●	●	●
	EtherCAT	-	●	●	●	●
Max. number of switched poles on BUS		48	32	32	32	32
External control		●	●	-	●	●
Control over BUS		-	●	●	●	●
SWITCHING MODES	ON / OFF	●	●	●	●	●
	Burst	●	●	●	●	●
	Distributed full cycle	●	●	●	●	●
	Advanced full cycle	●	●	●	●	●
	Phase angle	-	-	●	-	●
	Soft start with time *	-	-	●	-	●
	Soft start with current limit *	-	-	●	-	●
	Voltage compensation	-	-	●	●	●
	True power compensation *	-	-	-	●	●
Monitoring of system parameters		●	●	●	●	●
SSR diagnostics		●	●	●	●	●
Load diagnostics		●	●	●	●	●
Over-temperature protection		●	●	●	●	●

* feature currently unavailable for RGC2/3P..N. To be released soon..

Notes:

- **RG..D..N** and **RG..CM..N** devices cannot be mixed in the same bus chain.
- The **NRG internal BUS cables** are proprietary cables to daisychain the RG..Ns on the NRG bus chain and to connect the NRG controller to the first RG..N.
- The **internal BUS terminator** is provided in the same package with the NRG controller and shall be plugged into the last RG..N in the NRG bus chain.

List of contents

NRGC-EIP
References 5
Structure 6
General data 7
Dimensions 7
Power supply specifications 7
Auto-addressing 8
Communications 9
Internal bus 9
Compatibility and conformance 10
Environmental specifications 11
LED indicators 11
Alarm management 12
Connection diagram 13
Mounting 14
Connection specifications 15

RCRGN 16

References

Order code

NRGC-EIP


Carlo Gavazzi compatible components


Description	Component code	Notes
Solid state relays	RG..CM..N	NRG solid state relays • **RGx1..CM..N -** 1-pole SSR with control and real-time monitoring via BUS • **RGC2/3P..N -** 2/3 pole SSR with control and real-time monitoring via BUS (NRGC-EIP requires FW V2.1.0 or later for compatibility with RGC2/3P..N**)**
NRG Internal BUS cables	RCRGN-010-2	10cm cable terminated at both ends with a microUSB connector. Packed x4 pcs.
	RCRGN-025-2	25cm cable terminated at both ends with a microUSB connector. Packed x1 pc.
	RCRGN-075-2	75cm cable terminated at both ends with a microUSB connector. Packed x1 pc.
	RCRGN-150-2	150cm cable terminated at both ends with a microUSB connector. Packed x1 pc.
	RCRGN-350-2	350cm cable terminated at both ends with a microUSB connector. Packed x1 pc.
	RCRGN-500-2	500cm cable terminated at both ends with a microUSB connector. Packed x1 pc.

Further reading

Information	Where to find it	
User manual NRGC EtherNet/IP	https://gavazziautomation.com/images/PIM/MANUALS/ENG/SSR_UM_NRG_EIP.pdf	
Datasheet RGx1..CM..N (1-pole SSR with control and real-time monitoring via BUS)	http://gavazziautomation.com/images/PIM/DATASHEET/ENG/SSR_RG_CM_N.pdf	
Datasheet RGC2/3P..N (2/3-pole SSR with control and real-time monitoring via bus)	http://gavazziautomation.com/images/PIM/DATASHEET/ENG/SSR_RGC_2_3_N.pdf	
EDS file	http://www.gavazziautomation.com/images/PIM/OTHERSTUFF/EDS/EDS_NRGC-EIP.zip	

Structure





Bottom view


Element	Component	Function
Us+ Us-	Supply connection	2 position spring plug – Us-, Us+ connection for powering the NRGC-EIP
Push button	Communications check & Autoaddressing button	Enables and disables a Communications Check function of the BUS chain (link between NRGC-EIP and RG..Ns) by pressing front button between 2 to 5 seconds Enables auto addressing of RG..Ns when pressed for 3 seconds during power up. Check 'Autoaddressing' section for more info.
MAC address	Device MAC address	Increment by 1 and 2 for MAC addresses of X1 and X2
ON LED	ON indicator	Indicates presence of supply voltage on NRGC-EIP
BUS LED	BUS indicator	Indicates ongoing communication with RG..Ns
MS LED	Module status	Indicates the status of the device
NS LED	Network status	Indicates the status of the EtherNet/IP network interface
ALARM LED	ALARM indicator	Indicates presence of an alarm condition
Link / ACT LEDs	Link/Activity indicators	Indicates the status of the physical Ethernet connection
X1, X2	Ethernet ports	2x RJ45 plugs for EtherNet/IP communication
BUS	Micro-USB port – internal BUS	RCRGN cable connection for the internal BUS communications line

Features

General data

Material	Noryl (UL94 V0), RAL7035
Mounting	DIN rail
Dimensions	2-DIN
Touch protection	IP20, IP00 with door flap on front facade open
Weight	142g
Compatibility	RGC..CM..N 1-pole solid state contactors (RG end-devices) RGS..CM..N 1-pole solid state relays (RG end-devices) RGC2/3P..N 2-pole, 3-pole solid state contactors (RG end-devices)

Dimensions



All dimensions in mm.
Tolerances +/- 0.5 mm.

Performance


Power supply specifications

Supply port rating, Us	24 VDC
Supply voltage range, Us	19.2 – 32 VDC*
Reverse polarity protection	Yes
Consumption	< 12 W
LED Indication, Supply ON	Green LED
Power on	2 s

* to be supplied by class 2 power source according to UL1310

Auto-addressing

The RG..Ns on the bus chain are automatically addressed upon the first start-up of the system. The RG..Ns are addressed based on their position on the bus chain.



In case of an RG..N replacement, or any changes to the NRG bus chain, the RG..Ns have to be re-addressed. Follow the procedure below to re-address the RG..Ns on the NRG bus chain manually. Alternatively, auto-addressing can be done via an 'Explicit' command (check NRG EtherNet/IP User Manual for further information)




Fig. 1 *Hold the blue button while powering up the NRGC-EIP*




Fig. 2 *Release when Alarm LED turns ON indicating that autoaddressing is complete*

Communication

Communication protocol to Main Controller	EtherNet/IP™
EDS file	The EDS file for the NRGC-EIP is available electronically by going to www.gavazziautomation.com
IP address	The NRGC-EIP obtains its IP address via a DHCP service. The device is shipped with the Address Conflict Detection (ACD) function activated. Therefore, the device releases its IP address if the same IP address has been assigned multiple times in the network. ACD can be deactivated via the TCP/IP interface class
Connections	With the NRGC-EIP there are 2 possible connections: **Exclusive owner connection** - this connection is the main IO connection to control and read parameters from each NRG solid state relay. **Input only connection** - this connection is used to transfer the alarming data from each NRG solid state relay At least an Exclusive owner connection is required to initiate communication with the NRGC-EIP
Communication interface	The ethernet ports (X1, X2) are 100 Mbit, full duplex operation ports and should be connected to another EtherNet/IP device with Cat5e (straight through) cable via the standard RJ45 connector. It is recomended that the interconnecting cables should be fitted with plugs provided with an outer metallic shell with the shell connected to the wire screen of the cable. For further information refer to the EtherNet/IP cabling guidelines
LED indication - ACT	Yellow, Flashing - NRGC-EIP is sending/receiving Ethernet frames
LED indication - Link	Green, ON - Device is linked to Ethernet

Internal Bus

Max. number of RG..Ns connected to NRGC-EIP	32x switched poles of the RG..CM..N solid state relays
Connection to RG..Ns	RCRGN-xx 5-way cable terminated with micro-USB connection
BUS termination	RGN-TERMRES (1x pc. provided with 1x NRGC-EIP) to be plugged on the last RG..N on the BUS chain to terminate the internal BUS
LED indication - BUS	Yellow, ON indicating ongoing communication with the RG end-devices

Compatibility and Conformance

Approvals	CE cULus LISTED EAC
Standards compliance	LVD: EN 60947-5-1 EMCD: EN 60947-5-1 UL: UL508 (E172877), NMFT cUL: C22.2 No. 14 (E172877), NMFT7

Electromagnetic compatibility (EMC) - Immunity	
Electrostatic discharge (ESD)	EN/IEC 61000-4-2 8 kV air discharge, 4 kV contact (PC1)
Radiated radio frequency	EN/IEC 61000-4-3 10 V/m, from 80 MHz to 1 GHz (PC1) 10 V/m, from 1.4 to 2 GHz (PC1) 3 V/m, from 2 to 2.7 GHz (PC1)
Electrical fast transient (burst)	EN/IEC 61000-4-4 Input: 1 kV, 5 kHz & 100 kHz (PC1) Internal bus: 1 kV, 5 kHz & 100 kHz (PC1) EtherNet/IP ports: 1 kV, 5 kHz & 100 kHz (PC1) 2 kV, 5 kHz & 100 kHz (PC2)
Conducted radio frequency	EN/IEC 61000-4-6 10 V/m, from 0.15 to 80 MHz (PC1)
Electrical surge	EN/IEC 61000-4-5 DC Output / Input, line to line: 500 V (PC2) DC Output / Input, line to earth: 500 V (PC2) Signal, line to earth 1 kV (PC2)[1]
Voltage dips and interruptions	EN/IEC 61000-4-11 0% @ 5000 ms (PC2) 40% @ 200 ms (PC2) 60% @ 10, 30, 100, 300, 1000 ms (PC2)
Voltage dips and interruptions on input lines	EN/IEC 61000-4-29 0% @ 1, 3, 10, 30, 100, 300, 1000 ms (PC2) 30% @ 10, 30, 100, 300, 1000 ms (PC2) 70% @ 10, 30, 100, 300, 1000 ms (PC2) 80% @ 10, 30, 100, 300, 1000 ms, 3 s, 10 s (PC2) 120% @ 10, 30, 100, 300, 1000 ms, 3 s, 10 s (PC2)

1. Not applicable to shielded cables <10m. Additional suppression on data lines may be required if shielded cables are not used.

Electromagnetic compatibility (EMC) - Emissions	
Radio interference field emission (radiated)	EN/IEC 55011 Class A: from 30 to 1000 MHz
Radio interference voltage emissions (conducted)	EN/IEC 55011 Class B: from 0.15 to 30 MHz


Environmental specifications

Operating temperature	-20 to +65 °C (-4 to +149 °F)
Storage temperature	-20 to +65 °C (-4 to +149 °F)
Relative humidity	95% non-condensing @ 40°C
Pollution degree	2
Installation altitude	0 - 2000m
EU RoHS compliant	Yes
China RoHS	

LED indicators

ON	Green	ON:	Us is present at terminals Us+, Us-
		OFF:	Us is not present at terminals Us+, Us-
Link (X1 & X2)	Green	ON:	Device is linked to Ethernet
		OFF:	Device has no link to Ethernet
ACT (X1 & X2)	Yellow	OFF:	No frames are being sent/received
		Flashing:	NRGC-EIP is sending/receiving Ethernet frames
BUS	Yellow	ON:	During transmission of messages from NRGC-EIP to RG..Ns
		OFF:	Idle bus between the NRGC-EIP and RG..Ns and when NRGC-EIP is receiving data from RG..Ns
ALARM	Red	ON:	Flashing when alarm condition on NRGC-EIP is present. Refer to Alarm management section
		OFF:	No alarm condition
MS	Red Green	Green:	NRG Controller is operational
		Green Flickering:	NRG Controller has not been configured
		Green / Red Flickering:	NRG Controller is performing its power-up testing
		Red:	NRG Controller has detected a major unrecoverable fault
		Red Flickering:	NRG Controller has detected a major recoverable fault
		OFF:	NRG Controller is powered off
NS	Red Green	Green:	Connected: An IP address is configured and at least one CIP connection is established
		Green Flickering:	No connections: an IP address is configured but no CIP connections are established
		Green / Red Flickering:	NRG controller is performing its power-up testing
		Red:	Duplicate IP: NRG controller detected that its IP address is already in use
		Red Flickering:	Connection time-out an IP address is configured and Exclusive Owner connection has timed out
		OFF:	NRG controller does not have an IP address or is powered off

Alarm management

<table>
<tr><td>Alarm condition present</td><td colspan="2">• ALARM LED ON with a specific flashing rate
• Alarms are also available as implicit messages via the Ethernet/IP communication interface. Refer to NRG EtherNet/IP User Manual for further information</td></tr>
<tr><td rowspan="6">Alarm types</td><td>No. of flashes</td><td>Description of fault</td></tr>
<tr><td>2</td><td>Errors in the configurations of the internal NRG bus chain including:
• Number of RG..Ns on bus chain is > 32 (Device Limit Error)
• More than one RG..N on the bus chain have the same address (Device conflict error)
• One of the RG..Ns does not have an address. This may occur when a new RG..N is introduced to the bus chain (Device Unconfigured Error)
• The internal Device ID of one of the RG..Ns on the bus chain does not correspond to its position on the bus (Device Position Error)</td></tr>
<tr><td>4</td><td>Supply Error:
Supply to NRGC-EIP is outside of the specified range</td></tr>
<tr><td>8</td><td>Communication Error (BUS):
An error in the communication link (internal BUS) between the NRGC-EIP and RG..Ns</td></tr>
<tr><td>9</td><td>Internal Error:
Detection of internal issues with the NRGC-EIP</td></tr>
<tr><td>10</td><td>Termination (BUS) Error:
Internal BUS chain not terminated</td></tr>
<tr><td>Flashing rate</td><td colspan="2">
</td></tr>
</table>

Connection diagram

The NRG bus chain can be configured in a EtherNet/IP network via a line, ring, star or tree topologies via the ethernet ports on the NRGC-EIP.




Fig. 3 *Example of a line configuration of the NRGC-EIP with other EtherNet/IP devices and controller*






Fig. 4 *Example of a star configuration of the NRGC-EIP with other EtherNet/IP devices and controller*

Mounting


Mounting on DIN rail



Dismounting from DIN rail



Connection specifications

Power connection	
Terminal	Supply: Us+, Us-
	 Top view
Conductors	Use 60/75°C copper (Cu) conductors
Stripping length	12 - 13 mm
Connection type	2-pole spring plug, pitch 5.08 mm
Rigid (solid & stranded) UL/CSA rated data	0.2 – 2.5 mm², 26 – 12 AWG
Flexible with end sleeve	0.25 – 2.5 mm²
Flexible without end sleeve	0.25 – 2.5 mm²
Flexible with end sleeve using TWIN ferrules	0.5 – 1.0 mm²

Communication - connection	
Terminal	X1, X2: RJ45 (x2) BUS: RCRGN-xxx-2
	 Bottom view
EtherNet/IP connection	RJ45 shielded plugs
Cable for EtherNet/IP	Not provided. Check EtherNet/IP cabling guidelines for further info.
Max. length of Ethernet cable	100 mtrs (between EtherNet/IP devices)
Cable for Internal Bus	RCRGN-xxx-2: 5-way USB micro connection - +24 supply line for RG..Ns - GND - RS485A - RS485B - Autoconfig / Auto addressing line

RCRGN..

NRG internal BUS cable



Main features

- Cables available at various lengths for the internal BUS of the NRG system
- Cables terminated at both ends with a microUSB plug
- Connects the NRG controller to the RG..N solid state relay and respective RG..N solid state relays

Description

The **RCRGN** cables are proprietary cables that must be used with the NRG system for the internal BUS. These cables are 5-way cables carrying the communication, supply and autoconfiguration / auto-addressing lines. By means of autoconfiguration / auto-addressing, the RG..Ns are assigned a unique ID based on the physical location and on the internal BUS.

Carlo Gavazzi compatible components

Description	Component code	Notes
NRG Controller	NRGC..	NRG controllers: Modbus, Modbus TCP, PROFINET, EtherNet/IP, EtherCAT 1x **RGN-TERMRES** is included in the NRGC.. packaging. The RGN-TERMRES is to be mounted on the last RG..N on the bus chain.
Solid state relays	RG..N	NRG solid state relays

Order code

RCRGN - □ - 2

Enter the code entering the corresponding option instead of □

Code	Option	Description	Notes
RCRGN	**-**	Cables suitable for the NRG system	
□	**010**	10 cm cable length	packed x 4 pcs.
	025	25 cm cable length	packed x 1 pc.
	075	75 cm cable length	packed x 1 pc.
	150	150 cm cable length	packed x 1 pc.
	350	350 cm cable length	packed x 1 pc.
	500	500 cm cable length	packed x 1 pc.
2	**-**	Terminated at the both ends with a microUSB connector	

COPYRIGHT ©2026
Content subject to change.
Download the PDF: http://www.gavazziautomation.com